

OPERATING LIMITS

DENSITY ALTITUDE	CALIBRATED AIRSPEED - KNOTS			
	6600 LB	7500 LB	8500 LB	9500 LB
SL-2000 FT	112	112	107	103
3000 FT	109	109	104	100
6000 FT	100	100	95	91
9000 FT	91	91	86	82
12000 FT	82	82	77	73
15000 FT	70	70	65	---
18000 FT	58	58	---	---

UP TO 7500 LBS GW USE 6000 TO 6600 RPM RANGE

OVER 7500 LBS GW USE 6400 - 6600 RPM RANGE

REDUCE AIRSPEED WHEN VIBRATIONS IS EXCESSIVE

THIS HELICOPTER MUST BE OPERATED
IN COMPLIANCE WITH THE OPERATING
LIMITATIONS SPECIFIED IN THE FAA
APPROVED MOTORCRAFT FLIGHT MAN.

GAS PRODUCER SPEED LIMIT

MAXIMUM GAS PRODUCER SPEED:

TAKE - OFF POWER: 99.9%

MAX TORQUE POWER: 92.9%

PILOT'S CHECK LIST

UH-1H

TAKE OFF

1. INSTRUMENTS
2. CONTROLS
3. GOVERNOR RPM

LANDING

1. COLL FRICTION
2. HARNESS
3. GOVERNOR RPM

FOR DETAILED INSTRUCTIONS
REFER TO TM 55-1520-219-10